

Gamma CP

Codice	Modello	Capacità	Diametro	Altezza	Raccordo ingresso acqua	Pressione di precarica standard	Pressione massima di esercizio	Temperatura di esercizio	Finitura esterna colore
		Litri	Ø mm	H mm	G	Bar	Bar	°C	
7506	CP335 / 6	6	326	118	M 3/4" Gas	1,5	3,0	-10 + 90	Rosso
7508	CP335 / 8	8	326	132	M 3/4" Gas	1,5	3,0	-10 + 90	Rosso
7510	CP335 / 10	10	326	148	M 3/4" Gas	1,5	3,0	-10 + 90	Rosso
7512	CP335 / 12	12	326	170	M 3/4" Gas	1,5	3,0	-10 + 90	Rosso
7405/001	CP364 / 5	5	364	59	M 3/8" Gas	1	3,0	-10 + 90	Rosso
7407/001	CP364 / 7	7	364	92	M 3/8" Gas	1	3,0	-10 + 90	Rosso
7606	CP387 / 6	6	387	93	M 3/4" Gas	1,5	3,0	-10 + 90	Rosso
7607	CP387 / 7	7	387	97	M 3/4" Gas	1,5	3,0	-10 + 90	Rosso
7608	CP387 / 8	8	387	109	M 3/4" Gas	1,5	3,0	-10 + 90	Rosso
7610	CP387 / 10	10	387	128	M 3/4" Gas	1,5	3,0	-10 + 90	Rosso
7612	CP387 / 12	12	387	142	M 3/4" Gas	1,5	3,0	-10 + 90	Rosso
7614	CP387 / 14	14	387	170	M 3/4" Gas	1,5	3,0	-10 + 90	Rosso
7618	CP387 CE / 18	18	387	181	M 3/4" Gas	1,5	3,0	-10 + 90	Rosso
760692	CP392 / 6	6	392	61	M 3/8" Gas	1	3,0	-10 + 90	Rosso
760892	CP392 / 8	8	392	73	M 3/8" Gas	1	3,0	-10 + 90	Rosso
761092	CP392 / 10	10	392	90	M 3/8" Gas	1	3,0	-10 + 90	Rosso
7706	CP416 / 6	6	415	65	M 3/8" Gas	1,5	3,0	-10 + 90	Grigio
7708	CP416 / 8	8	415	80	M 3/8" Gas	1,5	3,0	-10 + 90	Grigio
7710	CP416 / 10	10	415	90	M 1/2" Gas	1,5	3,0	-10 + 90	Grigio
7712	CP416 / 12	12	415	108	M 1/2" Gas	1,5	3,0	-10 + 90	Grigio